



T-Range: -60÷125 °C

Heat Shrinkable 2:1

COD.	SIZE	D	Wall thickness			
1601.001.01	0.7	0.9 ± 0.2	0.15 ± 0.1			200 m/roll
1601.001.02	1.0	1.5 ± 0.2	0.20 ± 0.1			
1601.001.03	1.5	2.1 ± 0.2	0.20 ± 0.1			
1601.001.04	2.0	2.6 ± 0.2	0.20 ± 0.1			
1601.001.05	2.5	3.1 ± 0.2	0.15 ± 0.1			
1601.001.06	3.0	3.6 ± 0.2	0.15 ± 0.1			
1601.001.07	3.5	4.1 ± 0.3	0.15 ± 0.1			100 m/roll
1601.001.08	4.0	4.6 ± 0.3	0.15 ± 0.1			
1601.001.09	4.5	5.1 ± 0.3	0.15 ± 0.1			
1601.001.10	5.0	5.6 ± 0.3	0.30 ± 0.1			
1601.001.11	5.5	6.1 ± 0.3	0.30 ± 0.1			
1601.001.12	6.0	6.6 ± 0.3	0.30 ± 0.1			
1601.001.13	6.5	7.1 ± 0.3	0.30 ± 0.1			
1601.001.14	7.0	7.6 ± 0.3	0.30 ± 0.1			
1601.001.15	8.0	8.6 ± 0.3	0.35 ± 0.1			
1601.001.16	9.0	9.6 ± 0.3	0.35 ± 0.1			
1601.001.17	10.0	10.3 ± 0.3	0.35 ± 0.1			
1601.001.18	11.0	11.6 ± 0.3	0.35 ± 0.1			
1601.001.19	12.0	12.7 ± 0.3	0.35 ± 0.1			
1601.001.20	13.0	13.7 ± 0.3	0.35 ± 0.1			
1601.001.21	14.0	14.7 ± 0.4	0.35 ± 0.1			
1601.001.22	15.0	15.7 ± 0.4	0.35 ± 0.1			
1601.001.23	50.0	52.0 ± 0.5	0.50 ± 0.1			

Colour	Black	White	Grey	Transp.	Blue	Red	Green	Gold	Yellow	Natural	Chrome
Material											
EVA	320										