



T-Range: -60÷200 °C

COD.	D	Cat No 1200V 200°C Thickness ()	Cat No 1500V 200°C Thickness ()	Cat No 2500V 200°C Thickness ()	Cat No 4000V 200°C Thickness ()	Cat No 7500V 200°C Thickness ()	
1602.001.01	0.8	0.3	0.35	0.35	0.50	0.50	100m/roll
1602.001.02	1.0	0.3	0.35	0.35	0.50	0.50	
1602.001.03	1.5	0.35	0.35	0.40	0.50	0.50	
1602.001.04	2.0	0.35	0.35	0.40	0.50	0.50	
1602.001.05	2.5	0.35	0.35	0.40	0.55	0.50	
1602.001.06	3.0	0.35	0.35	0.40	0.55	0.50	
1602.001.07	3.5	0.35	0.35	0.40	0.55	0.50	
1602.001.08	4.0	0.40	0.40	0.45	0.60	0.50	
1602.001.09	4.5	0.40	0.40	0.45	0.60	0.50	
1602.001.10	5.0	0.40	0.40	0.45	0.60	0.50	
1602.001.11	5.5	0.40	0.40	0.45	0.60	0.50	
1602.001.12	6.0	0.40	0.40	0.45	0.65	0.50	
1602.001.13	7.0	0.40	0.45	0.45	0.65	0.50	
1602.001.14	8.0	0.45	0.45	0.50	0.70	0.50	
1602.001.15	9.0	0.45	0.45	0.50	0.70	0.50	50m/roll
1602.001.16	10.0	0.45	0.50	0.55	0.70	0.50	

Colour	Black	White	Grey	Transp.	Blue	Red	Green	Gold	Yellow	Natural	Chrome
Material											
SGF	360	361									