



























1x

Singolo isolamento FEP
FEP single insulation

| Codice Code | Colore guaina Sheath colour | mm ²  |  Ø mm | T _{max} °C | APPROVAL |  V |  |
|----------------|---|--|---|---------------------|----------|--|---|
| 92 |  | AWG22 | 1.2 | 180° | CE | 300/500 | CuSn |
| 93 |  | AWG22 | 1.2 | 180° | CE | 300/500 | CuSn |
| D8 |  | AWG22 | 1.2 | 180° | CE | 300/500 | CuSn |
| U1 |  | AWG22 | 1.2 | 180° | CE | 300/500 | CuSn |
| U2 |  | AWG22 | 1.2 | 180° | CE | 300/500 | CuSn |
| 01 |  | AWG20 | 1.6 | 180° | VDE | 300/500 | CuSn |
| 07 |  | AWG20 | 1.6 | 180° | VDE | 300/500 | CuSn |
| 45 |  | AWG20 | 1.6 | 180° | VDE | 300/500 | CuSn |
| 85 |  | AWG20 | 1.6 | 180° | VDE | 300/500 | CuSn |
| G8 |  | AWG20 | 1.6 | 180° | VDE | 300/500 | CuSn |
| 02 |  | AWG18 | 1.8 | 180° | VDE | 300/500 | CuSn |
| 08 |  | AWG18 | 1.8 | 180° | VDE | 300/500 | CuSn |
| C5 |  | 0.50 | 1.4 | 180° | IMQ | 300/500 | CuSn |
| P1 |  | 0.50 | 1.4 | 180° | IMQ | 300/500 | CuSn |
| P2 |  | 0.50 | 1.4 | 180° | IMQ | 300/500 | CuSn |
| P3 |  | 0.50 | 1.4 | 180° | IMQ | 300/500 | CuSn |
| P5 |  | 0.50 | 1.4 | 180° | IMQ | 300/500 | CuSn |
| B1 |  | 0.75 | 1.7 | 180° | IMQ | 300/500 | CuSn |
| D9 |  | 0.75 | 1.7 | 180° | IMQ | 300/500 | CuSn |